

Flexible Tubing

Polyethylene Low Density Tube

Applications: Pneumatic lines, vacuum equipment, oil & fuel lines, process control and air tools.

Couplings:

- PNPC*, PBPC*, BNPC*, SSPC* Push-in
- BRC* Compression
- BRB* Barb
- PLBI* Barb

Temperature: -0°C to +60°C

Conforming Standards: AS2070 for food contact.



* Standard colour is Black with options of Natural (N), Blue (BL), Red (R) and Green (G), add suffix to complete code.

OD	ID	WP PSI	BP PSI	Bend Radius	PRODUCT CODE	SUPPORT SLEEVE
Imperial						
1/4	0.164	120	360	1 1/2	TPIP04-100*	BRCI99-04
5/16	0.210	120	360	2	TPIP05-100*	BRCI99-05
3/8	0.250	120	360	2 3/4	TPIP06-100*	BRCI99-06A
1/2	0.375	120	360	3 1/2	TPIP08-100*	BRCI99-08A
5/8	0.500	120	360	4 3/4	TPIP10-100*	BRCI99-10
Metric						
04	2.5	120	360	28	TPMP04-100*	BRCM99-04
06	4.0	120	360	42	TPMP06-100*	BRCM99-06
08	6.0	120	360	56	TPMP08-100*	BRCM99-08A
10	7.5	120	360	70	TPMP10-100*	BRCM99-10
12	8.6	120	360	84	TPMP12-100*	BRCM99-12

Polyurethane Tube

Applications: Pneumatic lines, vacuum equipment, oil & fuel lines, process control and air tools.

Couplings:

- PNPC*, PBPC*, BNPC*, SSPC* Push-in
- BRC* Compression
- BRB* Barb

Temperature: -0°C to +60°C



* Standard colour is Black with options of Natural (N), Blue (BL), Red (R) and Green (G), add suffix to complete code.

Sizes 3/8, 1/2, 10mm, 12mm and 16mm only available in Black and Natural.

OD	ID	WP PSI	BP PSI	PRODUCT CODE	SUPPORT SLEEVE
Imperial					
3/16	0.125	130	360	TPIU03-100*	BRCI99-03
1/4	0.165	130	360	TPIU04-100*	BRCI99-04
5/16	0.190	130	360	TPIU05-100*	BRCI99-05
3/8	0.250	130	360	TPIU06-100*	BRCI99-06
1/2	0.335	130	360	TPIU08-100*	BRCI99-08
Metric					
04	2.0	130	360	TPMU04-100*	BRCM99-04
06	4.0	130	360	TPMU06-100*	BRCM99-06
08	5.0	130	360	TPMU08-100*	BRCM99-08
10	6.5	130	360	TPMU10-100*	BRCM99-10
12	8.0	130	360	TPMU12-100*	BRCM99-12