List price

1,500 PSI & 3,000 PSI ... DESIGNED TOUGH FOR AUSSIE CONDITIONS



Super Indy Mk3

Super Indy Mk 3

Model		Single Phase	Three Phase
Stock code		Next to price	Next to price
Safety Classification		Class A	
Pump pressure	psi	1,500 (100 bar)	3,000 (200 bar)
EWP with turbo	psi	2,600	4,785
Flow	lpm	12	16
Max temperature	°C	120	120
Motor	Phase	Single phase (240V)	Three phase (415V)
Power	kW	2.2kW	5.5kW
Pump speed	rpm	1450	1450
Pump type		Interpump triplex	Interpump triplex
Pump Model		EL1413	WS151DX
Nozzle size		055	045
Accessories - Hose		8M R2 hot water hose	
Gun		AL55 (M4022109010)	
Lance		700MM single (C3905.14)	
Nozzle type	Nozzle type	Laser cut tip	
Weight	kg	120	190
Boxed dimensions	LxWxH (mm)	1070 x 740 x 920	1070 x 740 x 920
	Mild steel coil (DS)	(FS/INDDS1012MV3)	(FS/INDDS2016TV3)

- Slow speed, 4 pole, IP56 motor (1400 rpm) for reliable long life performance
- Heavy duty slow speed triplex pump with brass head & ceramic pistons
- Mild steel heavy duty coil with 2 year coil warranty, stainless steel coil option with 3 year coil warranty
- Low water cut-out warning light control, prevents damage to machine
- Low fuel sensor & warning light
- 18 litre diesel fuel tank
- Timed Total Stop—auto shut down
- High pressure detergent injection
- Stainless steel cover, 250mm wheels & heavy duty steel chassis with bumper
- Safety thermostat to protect pump
- Flexible coupling between motor and pump for a smoother, cooler drive.
- Micro-leak detection with warning light
- Class A ... no operator certification required

MADE TOUGH FOR TOUGH AUSSIES



Wet/Dry Vacs ... SUPER SUCKERS

Hose Reels ... EXTEND HOSE LIFE

Pick up waste water or use

10 litres

30 litres

75 litres

Store extra length hoses,

to 5,000 psi, must be wall

for vehicle detailing

VF13

VC44


VC72

mounted.




Stainless steel coil (DX) (FS/INDDX1012MV3)





(FS/IND3DX2016T)



Optional accessories that turn these blasters into cleaning systems

Turbo Lance 60% MORE BITE Increase the effective working pressure (EWP)

of your blaster without loading the pump!

Personal Protective Gear to 500 bar

Overalls

CTN255- (insert nozzle size)

CLEAN FLAT SURFACES FAST

SLASH CLEANING TIMES BY 75% Stainless steel flat surface cleaners

Clean four times faster, leaving a streak free finish. Standard nozzles included

AGPDFSC22Z (22" dia, 80°C max) HANT28 (28" dia, 120°C max) HANT4C (Multi-Twister, 120°C max)

Extra length hose ... MORE CONVENIENT

Cleaning large plant?... reach all the wa around with these extra length hoses, 5,800 psi rated, R2 wire braid hose,


3/8F ends, see p 64/65 for couplings

AHW06FB6FB6X10 (10m) AHW06FB6FB6X20 (20m) AHW06FB6FB6X30 (30m)AHW06FB6FB6X50 (50m)



p 69

Hose & whip hose sold separately (see p 68)



HAR150 (holds up to 45m) HAR151 (holds up to 75m)

Gloves

Boots