# PRODUCT SPECIFICATION



## VYRSA Model VYR-25 Impact Sprinkler

## Application:

The sprinkler VYR-25 is an agricultural model low-flow full circle made of brass and has a ½" male connection.

With a range of low flow nozzles for the VYR-25, this sprinkler is designed to work with a flow range between 9 and 31 l/min, at pressures between 150 and 350 KPA and cover a range of between 14 and 20 meters in diameter.

The sprinkler VYR-25 only has a single nozzle with a 24° angle.

The average time of rotation comes to be approximately 40sec and is ideal for under-tree and nursery applications.

#### Features:

- Brass Sprinkler
- 15mm Male Thread
- Full Circle
- 24° Nozzle Trajectory



#### Equivalent To:

Toro Premier

VYR-25										
	9/64" - 3.57mm		5/32" - 3.96mm		11/64" - 4.36mm		3/16" - 4.76mm		13/64" - 5.15mm	
KPA	LPM	RAD (M)	LPM	RAD (M)	LPM	RAD (M)	LPM	RAD (M)	LPM	RAD (M)
140	9.5	7.0	11.5	7.4	14.0	7.6	16.3	7.9	19.4	8.2
180	10.6	7.4	13.0	7.7	15.8	7.8	18.4	8.2	21.7	8.5
210	11.7	7.7	14.3	8.0	17.3	8.2	20.3	8.5	23.8	8.8
250	12.7	8.0	15.5	8.2	18.8	8.3	22.1	8.8	25.8	9.1
280	13.6	8.2	16.6	8.5	20.1	8.6	23.7	9.0	27.6	9.4
320	14.5	8.5	16.7	8.6	21.5	8.8	25.2	9.1	29.3	9.7
350	15.2	8.6	18.6	8.9	22.5	9.1	26.6	9.4	31.0	9.8

operation within the grey area is not recommended

MODELS	CODE		
15mm Impact Sprinkler Full Circle Brass Single Nozzle	VYR-25		

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE - PRODUCT DRAWINGS / IMAAGES ARE REPRESENTATIVE ONLY AND ARE SUBJECT TO CHANGE.