

Layflat Extruded

PLEW10 MAXIMUS Standard Duty

MAXIMUS LEW10 Standard Duty

Applications: Layflat hose for delivery of water, drainage, liquid fertilizers and agricultural chemicals. Can handle relatively small rises in elevation.

Not recommended for use with travelling irrigators.

Temperature: -20°C to +60°C
Cover: Blue, smooth PVC compound
Tube: Blue, smooth PVC compound
Reinforcement: High strength synthetic cord

Size	ID mm	OD mm	WP psi	BP psi	Weight Kg/mtr
25	26.5	29	100	305	0.16
32	33.5	36	100	305	0.22
38	39.0	42	90	262	0.26
51	52.0	54	60	175	0.30
63	65.0	68	60	175	0.33
76	77.0	80	60	175	0.40
102	103.0	106	60	175	0.62
127	128.0	133	60	175	0.90
152	153.0	160	60	175	1.15
203	207.0	212	45	130	1.80
254	257.0	263	36	115	2.60
305	308.0	314	30	90	2.90
354	359.0	365	30	90	3.90
406	410.0	416	30	90	4.60

PLEW12 MAXIMUS Heavy Duty

MAXIMUS LEW12 Heavy Duty

Applications: Abrasion and kink resistant heavy duty hose for discharging water in construction, mining, quarry, and industrial applications requiring higher working pressures.

Not recommended for use with travelling irrigators.

Temperature: -20°C to +60°C
Cover: Red, smooth PVC compound
Tube: Red, smooth PVC compound
Reinforcement: High strength synthetic cord

Size	ID mm	OD mm	WP psi	BP psi	Weight Kg/mtr
38	39.0	43	150	450	0.29
51	52.5	56	150	450	0.42
63	66.0	69	150	450	0.54
76	78.5	82	150	450	0.66
102	104.0	108	150	450	1.00
152	155.0	160	150	450	1.70
203	206.0	212	150	450	2.30