Food

PPDF10 Clear Vinyl Tubing



Applications: A non toxic clear tube suitable for the low pressure transfer of food and beverages.

-10°C to +60°C Clear, PVC compound Temperature: Cover: Clear, PVC compound Wall:

Reinforcement:

Size	ID mm	OD mm	WP psi	Weight Kg/mtr
3	3.2	5.2	125	0.017
4	3.9	7	120	0.035
5	4.8	8	115	0.042
6	6.3	9.4	90	0.048
8	7.9	11	75	0.061
10	9.5	13	60	0.074
10+	9.5	15	90	0.134
12	12.7	16.5	60	0.090
16	15.9	19.9	60	0.113
19	19.1	23	50	0.181
25	25.4	31	50	0.360
32	32.1	38	40	0.452
38	38.1	46	40	0.712
51	50.8	60.8	40	1.165

⁺ Cafeteria tube

PPDF14 EVA



Applications: Non-toxic, non-tainting tube widely used for soft drink lines, beer dispensing, drinking water conveyance and for liquefied food products with low to medium viscosity.

Conforming Standards: AS 2070

Temperature:

-10°C to +75°C Translucent, EVA compound Translucent, EVA compound Cover: Wall:

Reinforcement: Nil

Size	ID mm	OD mm	WP psi	Weight Kg/mtr
4	3.9	7	40	0.07
5	4.8	8	40	0.12
6	6.3	10	40	0.16
8	7.9	12.5	40	0.20
10	9.5	15	40	0.46
12	12.7	17.5	40	0.66

PPDF13 Drinking Water



Size	ID mm	OD mm	WP psi	BP psi	Weight Kg/mtr
12	12.7	17	110	440	0.23

Applications: For the conveying of drinking water, ideal for

caravans, boats, etc, will not taint the water

Conforming Standards: AS 2070.1 AS 4020 for food contact.

Temperature:

-5°C to +60°C White, smooth PVC compound with Cover:

Blue stripe Clear, PVC compound Fabric braid Tube:

Reinforcement:

