

Materials Handling

PHMS18 Air Seeder




Applications: Primary and secondary lines on air seeding equipment.

Temperature: -5°C to +60°C
Cover: Clear, slightly corrugated
Tube: Clear, PVC
Reinforcement: Anti-shock rigid black PVC helix

Size	ID mm	OD mm	WP psi	BP psi	B Rad mm	Vacuum %	Weight Kg/mtr
25	25.4	32.0	95	285	120	90	0.38
32	32.1	39.0	95	285	150	90	0.48
38	38.1	45.8	80	240	200	90	0.63
45	44.5	52.6	65	195	240	90	0.86
51	50.8	59.4	65	195	300	90	1.00
63	63.5	73.7	65	195	400	90	1.35

RWMD10 Don




Applications: Softwall bulk materials delivery hose for conveyance of cement dust, sand, gravel, silica and other abrasive materials.

Temperature: -40°C to +70°C
Cover: Black, smooth wrapped finish SBR rubber compound
Tube: Black, anti-static rubber compound
Reinforcement: High strength synthetic cord

Size	ID mm	OD mm	WP psi	BP psi	Weight Kg/mtr
102	101.6	119	75	225	3.10

RWMD11 MAXIMUS Dry Materials Delivery



Applications: Softwall bulk materials delivery hose for conveyance of cement dust, sand, gravel, silica and other abrasive materials.

Temperature: -20°C to +70°C
Cover: Black, smooth wrapped finish SBR rubber compound
Tube: Black, anti-static rubber compound
Reinforcement: High strength synthetic cord

Size	ID mm	OD mm	WP psi	BP psi	Weight Kg/mtr
102	101.6	120	90	270	3.10