


Materials Handling

RWMD20 Seeder



Applications: Delivery of grain to primary and secondary lines on air seeding equipment, resistant to weather, ozone and abrasion.

Temperature: -30°C to +70°C
Cover: Black, smooth wrapped finish EPDM rubber compound
Tube: Black, NR/SBR rubber compound
Reinforcement: High strength synthetic cord plus embedded steel helix wire

Size	ID mm	OD mm	WP psi	BP psi	Band mm	Weight Kg/mtr
32	32.1	42.0	45	135	135	0.90
38	38.1	49.5	45	135	160	1.32
45	44.5	57.0	45	135	180	1.51
51	50.8	62.5	45	135	225	1.70
63	63.5	75.0	45	135	285	2.40
76	76.1	89.5	45	135	360	3.50

RWMD22 RC Sampling



Applications: Specifically designed for use on reverse cycle drilling equipment to transfer dry abrasive materials.

Temperature: -20°C to +70°C
Cover: Black, smooth wrapped finish SBR rubber
Tube: Black, smooth abrasion resistant rubber compound
Reinforcement: High strength synthetic cord plus embedded steel helix wire

Size	ID mm	OD mm	WP psi	BP psi	Band mm	Weight Kg/mtr
51	50.8	83	500	1500	430	3.24
63	63.5	98	500	1500	510	3.75
76	76.1	108	500	1500	602	6.10
102	101.6	137	500	1500	700	8.32