

# Hose Protection Products

## Whip Checks

### Material Specifications:

Galvanised steel cables with crimped Aluminium ferrules.

### Applications:

Used as a safety measure on air hoses, spring loaded loops are fixed either side of connecting coupling. In the event of disconnecting, the whip check grips the hose and minimises the hose whipping around.



| Hose Size (in) | Length (in) | PRODUCT CODE |
|----------------|-------------|--------------|
| 10-32          | 14          | STWC-01032   |
| 32-51          | 38          | STWC-03251   |
| 63-102         | 48          | STWC-063102  |

## Whip Stocking - Double Eye



### Material Specifications:

Galvanised steel wiring, alloy ferrules.

### Applications:

Developed to handle higher pressure applications encountered in mining and construction industries, this stocking covers the hose. In the event of hose failure or disconnection, the hose whip is minimised.

| Hose OD | Grip Length (mm) | Aggregate breaking strength of all stands (Kn) | Tensile Strength (Kn) | PRODUCT CODE |
|---------|------------------|--|-----------------------|--------------|
| 19-28   | 800              | 100  | 62                    | SGHWS2C-028  |
| 28-40   | 900              | 100  | 62                    | SGHWS2C-040  |
| 40-50   | 500              | 38   | 23                    | SGHWS2C-050  |
| 50-60   | 600              | 57   | 24                    | SGHWS2C-060  |
| 60-70   | 800              | 57   | 24                    | SGHWS2C-070  |
| 70-85   | 1000             | 100  | 62                    | SGHWS2C-085  |
| 85-100  | 1000             | 158  | 98                    | SGHWS2C-100  |
| 100-120 | 1200             | 158  | 98                    | SGHWS2C-120  |
| 120-150 | 1400             | 211  | 186                   | SGHWS2C-150  |
| 150-190 | 1600             | 305  | 280                   | SGHWS2C-190  |

Other variations with Stainless Steel wire, copper ferrules or single offset eye are also available.