

Product information

CHDCE5055 - Danflon SS Fluoropolymer Hose

Designed for suction and discharge of the most aggressive chemicals and searching solvents and is generally used where the chemical resistance of polypropylene is inadequate. Suitable for the transfer of certain liquid food products.

Tube:	Ethylene Chloro Tri Fluoro Ethylene (ECTFE)
Cover:	Blue PVC coated polyester cloth with white layline
Reinforcement:	Fabric: Polyester Inner Wire: Stainless Steel 316 Outer wire: Stainless Steel 316
Temperature:	-30°C to +80°C
Conforming Standards:	BS EN 13765 Type 3 Heavy duty hose meets International Maritime Org IBC Code US Coastguard Requirements

Branding:



Hose Size (mm)	ID mm	WP Kpa	BP Kpa	Vacuum Kpa	Safety Factor	Bend Radius mm	Weight Kg/mtr
25	25.4	1400	5600	100	4:1	100	0.8
40	38.1	1400	5600	100	4:1	140	1.2
50	50.8	1400	5600	100	4:1	180	1.9
65	63.5	1400	5600	100	4:1	205	2.5
80	76.1	1400	5600	100	4:1	280	3.0
100	101.6	1400	5600	100	5:1	400	5.2
100L	101.6	1400	7000	100	5:1	400	6.4
150	152.4	1400	7000	100	5:1	510	10.7
200	203.2	1400	7000	100	5:1	760	15.0