

## PHPS02 MAXIMUS Blue Oil Suction

Suction and delivery of hydrocarbon materials such as diesel oils, grease, lubricants and most chemicals. Nitrile blend provides good flexibility and chemical resistance.

<b>Tube</b>	Light Blue, smooth PVC / Nitrile blend compound
<b>Cover:</b>	Light Blue, slightly corrugated PVC / Nitrile compound
<b>Reinforcement:</b>	Anti-shock rigid PVC helix
<b>Temperature:</b>	-20°C to +60°C

**Branding:**



Size	ID mm	OD mm	WP psi	BP psi	B Rad mm	Vacuum %	Weight Kg/mtr
25	25.4	32	75	225	80	85	0.39
32	32.1	39	75	225	100	85	0.51
38	38.1	46	65	195	150	85	0.65
51	50.8	60	65	195	200	85	1.10
63	63.5	75	60	180	250	85	1.50
76	76.2	87	55	165	300	85	1.80
102	101.6	115	55	165	375	85	3.01

DS-PHPS02

ISSUED: SEP 2014

REV: MAY 2019

**1300 BATSALES** [sales@batind.com.au](mailto:sales@batind.com.au)  
1300 228 725

visit our website [www.batind.com.au](http://www.batind.com.au)