

Polyurethane

DUUAS14 PUH A/S



Applications:

Suction of granules, abrasive powders, saw dust. Resistant to mineral oils, chemicals, atmospheric agents and ozone.


Conforming Standards: UL94-V0

Construction: Translucent anti-static and flame retardent ether based Polyurethane reinforced with copper plated steel wire.

Temperature: -40°C to +90°C

Size	B Rad mm	Vacuum m H ₂ O	Weight g/m
38	20	0.40	0.160
51	26	0.40	0.440
63	32	0.40	0.530
76	38	0.40	0.740
90	45	0.40	0.865
102	51	0.30	0.865
114	60	0.25	1.045
127	64	0.25	1.375
152	76	0.20	1.610
160	80	0.15	0.860
180	90	0.15	0.965
203	102	0.10	1.930
254	127	0.10	2.405
305	153	0.08	3.130

DUUAS14E Polyflex Light



Applications:

Lightweight anti static product for suction of granules, abrasive powders and saw dust.

Construction: Polyurethane / Polyester with spring steel wire. Unique organic compound attracts air borne moisture to create a continuous circuit that removes static build up as products pass through.

Temperature: -40°C to +100°C

Size	B Rad mm	Vacuum Bar	Weight g/m
38	28	0.25	0.230
51	35	0.20	0.300
63	42	0.16	0.342
76	53	0.10	0.430
90	63	0.10	0.485
102	70	0.09	0.510
127	88	0.08	0.650
152	105	0.06	0.780
160	109	0.06	0.806
180	123	0.05	0.901
203	140	0.05	1050
254	175	0.04	1250
305	210	0.03	1550